Sigen Power Sensor



- 1% high-accuracy power detection for precise control
- LCD real-time info display, easy to operate and check
- Integrates smoothly with Sigenergy devices, no need for setup
- Support export/import limitations and ready for AI evolving
- 100 ms data refresh rate, instantaneous data feed

Sigen Power Sensor

Sigen Sensor [1]	TP-CT120-DH	TP-CT300-DH	TP-CT600-DH	Units
Power Supply				
Grid connection type		3P3W/3P4W		
AC input voltage range		173 - 480		Vac
Nominal AC frequency		50 / 60		Hz
Measurement Accuracy				
Voltage accuracy		0.5%		
Current accuracy		0.5%		
Power accuracy		1%		
Frequency accuracy		0.2%		
Communication				
Interface		RS485		
Baud rate		9600		bps
Protocol		Modbus RTU		
General Data				
Dimensions (W / H / D)		72 / 94.5 / 65		mm
Weight	0.20	0.20	0.23	kg
Storage temperature range		-40 ~ 85		°C
Operating temperature range		-30 ~ 60		°C
Relative humidity range		0% ~ 90%		
Ingress protection rating		IP51		
Installation method		DIN Rail 35 mm		
CT Accessory				
Number of CT	3	3	3	pcs
Cable length of CT	1	1	1	m
Inner diameter of CT	16	24	36	mm
Weight of CT	0.09	0.2	0.4	kg
Max. operating current of CT	120	300	600	A
Standard Compliance				
Standard		EN 61010-1:2010, EN 61010-2-030:2010		

1. For more models refer to the Sigenergy website.

Disclaimer: The information in this file is provided on an "as is" basis. To the fullest extent permitted by law, Sigenergy Technology Co., Ltd. excludes all representations and warranties relating to this file and its contents or which is or may be provided by any affiliates or any other third party, including in relation to any inaccuracies or omissions in this file.